

## METHOD OF LOADING INITIAL PROGRAM IN PROCESSOR SYSTEM

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           The present invention relates to an initial program loading (IPL) operation in a processor system.

#### Related Background Art

10           Fig. 4 is a block diagram showing the configuration of a conventional processor system in which IPL operation is performed. Fig. 5 is a flowchart of the basis operation of the conventional system in an IPL operation mode and in a normal start mode.

15           In the system shown in Fig. 4, the IPL operation mode is selected by an operation mode selection switch 43 (step S501), and a central processing unit (CPU) 40 starts operating (step S502). The CPU 40 then loads an initial program loader (hereinafter referred to simply as "initial program" or "IPL program") held in a read-  
20           only memory (ROM) 41 added as an IPL storage to the processor system, and starts the initial program (step S503).

25           The CPU 40 initializes a communication portion 45 (sets communication conditions) by the started initial program (step S504), and downloads a system program from the outside of the processor system through a communication port 46. Writing of the downloaded

system program to a random access memory (RAM) 42 or the like connected to the system is continued until the communication is finished (steps S505, S506). When the communication is finished, the downloaded system  
5 program is started (step S507). On the other hand, when a normal start mode is selected by the operation mode selection switch 43, the CPU starts operating in the normal mode and performs the normal operation (steps S508, S509).

10 As described above, for conventional processor systems, a method is generally used in which an initial program is provided in advance by being written into the ROM 41 or the like added to the processor system, and the initial program is loaded from the ROM 41 or  
15 the like added to the processor system when the IPL operation mode is selected.

In the conventional system, however, it is difficult to rewrite the IPL program if the IPL program is provided by being written into a non-rewritable. To  
20 rewrite IPL program, it is necessary to change the ROM or to use an erasing and writing device specially provided for the ROM.

Further, having an IPL-storage ROM necessitates a special circuit for access the ROM, and different  
25 erasing and writing methods are required with respect to different ROM manufacturers or various types of IPL-storage ROM. To enable interchange or replacement of

ROMs, therefore, it is necessary to select the circuit configuration and the control method suitable for ROMs to be used.

5 SUMMARY OF THE INVENTION

The present invention has been made in view of the above, an object of the present invention is to provide a system or method for enabling an IPL program to be easily changed.

10 According to one aspect, the present invention which achieves this objective relates to a processor system comprising a central processing unit, a writeable memory, means for external communication, operation mode selection means for selecting an  
15 operation mode, control means for stopping the operation of the central processing unit and writing to the memory an IPL program transferred from the outside through the communication means when an IPL operation mode is selected by the operation mode selection means,  
20 and for thereafter canceling the stoppage of the operation of the central processing unit, and IPL operation means for executing the IPL program written to the memory through the operation of the central processing unit to download a system program.

25 According to another aspect, the present invention which achieves the above objective relates to a method of starting a processor system having a central

processing unit, a writeable memory, and a  
communication portion for external communication, the  
method comprising the steps of stopping the operation  
of the central processing unit when an IPL operation  
5 mode is selected, writing to the memory an IPL program  
transferred from the outside through the communication  
portion, canceling the stoppage of the operation of the  
central processing unit after the writing, and  
executing the IPL program written to the memory through  
10 the operation of the central processing unit to  
download a system program.

Other objectives and advantages besides those  
discussed above shall be apparent to those skilled in  
the art from the description of preferred embodiments  
15 of the invention which follow. In the description,  
reference is made to accompanying drawings, which form  
a part thereof, and which illustrate an example of the  
invention. Such example, however, is not exhaustive of  
the various embodiments of the invention, and therefore  
20 reference is made to the claims which follow the  
description for determining the scope of the invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the  
25 configuration of a processor system which performs an  
IPL operation in an embodiment of the present  
invention;

Fig. 2 is a diagram showing an example of address mapping in the IPL operation mode in the embodiment of the invention;

Fig. 3 is a flowchart of the basic operation in the IPL operation mode and in the normal start mode in the embodiment of the invention;

Fig. 4 is a block diagram showing the configuration of a conventional processor system which performs an IPL operation; and

Fig. 5 is a flowchart of the basic operation in the IPL operation mode and in the normal start mode in the conventional system.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings.

(First Embodiment)

A first embodiment of the present invention will be described with reference to the drawings.

Fig. 1 shows the basic configuration of a processor system in the first embodiment of the present invention. A CPU 10 shown in Fig. 1 executes a program to control each of portions of the system. This embodiment will be described by assuming that an address which the CPU 10 first reads immediately after startup (after activation from a reset state) is

"FFFF0".

A RAM 11 is provided in the processor system, and mapping on the RAM 11 is performed by assigning different addresses with respect to operation modes.

5 This embodiment is described by assuming that only one RAM 11 is provided. However, a plurality of rams may be provided.

10 An operation mode selection switch 12 determines an operation mode on startup. It is possible to select one of an IPL operation mode and a normal start mode as an operation mode at the time of startup by switching the operation mode selection switch 12. While the operation mode selection switch has been referred to as means for this mode selection, any selecting mechanism  
15 may be used for this mode selection as long as it is capable of selecting a particular operation mode from two or more operation modes.

20 An operation mode control unit 13 operates, on startup, according to the mode selected by the operation mode selection switch 12.

The operation mode control unit 13 has a mechanism which operates in the IPL operation mode, and which is constituted of a CPU deactivation portion 130 for stopping the CPU 10 from operating, a memory map  
25 switching portion 131 for changing memory address mapping, a communication condition setting portion 133 for initializing a communication portion 14 (setting

communication conditions), a data conversion portion  
134 for converting serial data into parallel data, a  
data writing portion 135 for writing data converted by  
the data conversion portion 134 to the RAM, and a  
5 transfer data termination detection portion 136 for  
detecting termination of transfer of data from the  
outside of the processor system. The memory map  
switching portion 131 also operates in the normal  
operation mode to perform mapping different from  
10 mapping in the IPL operation mode.

Thus, the operation mode control unit 13 has a  
plurality of functional portions capable of operating  
according to the operation mode.

Through the communication portion 14, the  
15 processor system performs communication with an  
external. This embodiment is described by assuming  
that only one communication portion is provided.  
However, a plurality of communication portions may be  
connected.

20 The communication portion 14 may operate based on  
any of communication systems or devices enabling  
communication with an external, such as a serial  
communication system (RS232C), a parallel communication  
system, USB, SCSI, a network, or a modem, and is not  
25 limited to a particular communication system.

This embodiment will be described by assuming that  
the communication system for the communication portion

14 uses RS232C for easy communication with personal computers. The reason for this selection is because "the communication control method is easy to perform", "the communication control method is simple", and "the communication protocols are fixed".

A communication port 15 is a unit for communication with an external. This embodiment is described by assuming that only one communication port 15 is provided. However, there is no problem even if a plurality of communication ports 15 are connected by being adapted to the communication portion 14.

Since in this embodiment the communication system of the communication portion 14 performs serial communication using RS232C, the embodiment is described by assuming the communication port 15 to be an RS232C serial communication port.

A ROM 16 has fixed information stored therein and is connected to the system. This embodiment is described by assuming that only one ROM 16 is provided. However, there is no problem even if a plurality of different ROMs are connected. Conversely, no ROM 16 may be connected.

A peripheral 17 is a peripheral device formed as a processor system. A plurality of similar peripherals may be connected and, conversely, no peripheral may be connected.

Fig. 2 is a diagram showing an example of address



mapping in a case where the operation mode selection switch 12 in the first embodiment selects the IPL operation mode when the operation of the processor system is started.

5           To an address range "0 to 7FFFF", nothing is mapped. The ROM 16 connected to the processor is mapped to an address range "80000 to F7FFF". A system program for the processor is downloaded to this ROM area. Also, the ROM area includes a portion capable of  
10 bank switching by an expanded memory specification (EMS), and the entire area of the ROM can be referred to through an EMS Window.

This address mapping is characterized in that a RAM incorporated in the system is mapped to an address range "F8000" to FFFFF" including the address "FFFF0" that the CPU 10 first reads immediately after startup.

An example of address mapping of the RAM 11 and the ROM 16 connected to the system has been described with reference to Fig. 2. The important point in this example is that a RAM area connected to the system is mapped to the address that the CPU 10 first reads immediately after startup.

That is, whatever the CPU, memory mapping may be  
freely performed, provided that a RAM area is mapped to  
the address first read immediately after startup.

Fig. 3 is a flowchart of the basic operation in the IPL operation mode and in the normal start mode.

The operation of the first embodiment will now be described with reference to Figs. 1, 2, and 3.

If the IPL operation mode is selected by the operation mode selection switch 12, address mapping in the processor system is as shown in Fig. 2.

The operation mode selection switch 12 is operated to select the operation mode (step S301). If the selected mode is the IPL operation mode, the operation mode control unit 13 issues from the CPU deactivation portion 130 a wait signal to stop the operation of the CPU 10. Upon receiving the wait signal, the CPU 10 becomes unable to operate (reset state)(step S302).

When the CPU 10 becomes unable to operate (reset state), the operation mode control unit 13 performs switching by the memory map switching portion 131 to address mapping corresponding to the IPL operation mode, i.e., that shown in Fig. 2 (step S303).

The operation mode control unit 13 then initializes the communication portion 14 (sets communication conditions) by the communication condition setting portion 133 (step S304).

When communication conditions of the communication portion 14 are determined, the operation mode control unit 13 starts downloading of an initial program from the outside of the processor via the communication port 15 (step S305).

After starting downloading of an initial program,

the operation mode control unit 13 receives data transmitted by serial communication (RS232C), converts the received data into parallel data by the data conversion portion 134, and writes the converted  
5 parallel data to the RAM 11 by the data writing portion 135 (step S306).

In this writing to the RAM 11 in the processor, the address that the CPU 10 first reads after activation from the reset state is set as a start  
10 address at which writing of data is started. Since in this embodiment the address the CPU 10 first reads on startup is "FFFF0", downloading is started by setting "FFFF0" as a data writing start address. When writing is advanced to address "FFFFF", downloading addressing  
15 jumps to the first address "F8000" of the RAM area, and downloading is again continued.

When a communication termination code indicating the completion of downloading of the initial program is received, the operation mode control unit 13 detects  
20 this communication termination code by the transfer data termination detection portion 136, and terminates the operation of downloading the initial program (IPL operation) (step S307).

In this embodiment, the downloadable maximum size  
25 of an initial program is automatically set to 32 kBytes at the time of address mapping shown in Fig. 2.

If an initial program having a size larger than 32

kBytes is received, overwriting of previously-received data is caused. Therefore, the operation mode control unit 13 is provided with a transfer data count portion 137, which enables termination of communication when  
5 the amount of data corresponding to 32 kBytes is received.

After terminating the IPL operation by detecting the time at which communication is to be terminated, the operation mode control unit 13 cancels the CPU  
10 deactivation signal (wait signal) from the CPU deactivation portion 130, and the CPU is allowed to operate while the selection of the IPL operation mode (address mapping shown in Fig. 2) is maintained (step S308). In other words, the reset of the CPU is removed  
15 in this step for the first time.

The downloaded initial program has been written from the start address corresponding to "FFFF0" on the RAM that the CPU first reads after being started. Therefore, when the CPU deactivation signal is  
20 canceled, the CPU starts reading the initial program to initiate the initial program on the RAM (step S309). Subsequently, downloading of a system program is performed based on the initial program (step S310).  
(Second Embodiment)

25 In the description of the first embodiment, the CPU deactivation signal issued from the CPU deactivation portion 130 is referred to as a wait

signal. However, a CPU resetting signal or the like may alternatively be used as long as the CPU can be deactivated.

(Third Embodiment)

5 In the description of the first embodiment, the transfer data termination detection portion 136 is assumed to detect the communication termination code. However, this method for detection by the transfer data termination detection portion is not exclusively used  
10 and any other method for detection of termination of communication may alternatively be used. For example, the communication data size may be set in advance, a termination data pattern of communication data may be set in advance, or a signal line for information of  
15 termination of communication may be used.

(Fourth Embodiment)

In the first embodiment, address mapping is changed according to the operation mode by the memory map switching portion 131. However, a method of  
20 connecting to different memories with respect to the operation modes by using a bus switching portion 132 capable of changing an address bus, a data bus, a signal line or the like may be used instead of the memory map switching method.

25 (Fifth Embodiment)

In this embodiment, an initial program is downloaded to the RAM 11 connected to the system and is

09770309.012904  
FOUO 8020/250

executed by the same method as that described above  
with respect to the first embodiment. However, a debug  
program for checking the operation of the peripheral 17  
connected to the system shown in Fig. 1 is included in  
5 the initial program downloaded to the RAM 11.

The peripheral operation checking debug program  
included in the initial program is executed after  
starting of the initial program to check whether the  
internal peripheral operates normally. This means is a  
10 simple but effective in checking the operation of the  
peripheral.

(Sixth Embodiment)

Also in this embodiment, an initial program is  
downloaded to the RAM 11 connected to the system and is  
15 executed by the same method as that described above  
with respect to the first embodiment. In this  
embodiment, a memory check program for checking the ROM  
16 connected to the processor system is included in the  
initial program downloaded to the RAM 11.

20 The memory check program included in the initial  
program is executed after starting of the initial  
program to ascertain whether there is a defect in the  
ROM 16 connected to the system before downloading of a  
system program.

25 The ROM connected to the system has been mentioned  
as an object of checking. However, each of a plurality  
of RAMS and ROMs connected to the system may also be

set as a checking object.

This method for memory checking achieves easier checking at a higher checking speed in comparison with the generally-practiced method using the Joint Test  
5 Action Group (JTAG).  
(Seventh Embodiment)

Also in this embodiment, an initial program is downloaded to the RAM 11 connected to the system and is executed by the same method as that described above  
10 with respect to the first embodiment. In this embodiment, a program for checking connections to peripherals connected to the processor system is included in the initial program downloaded to the RAM 11.

15 After starting the initial program, the peripheral connection check program incorporated in the initial program is executed. It is possible to easily detect a defective condition of connections of the peripherals in the processor system by executing the peripheral  
20 connection check program.

In the processor system in each of the above-described embodiments, an IPL program is downloaded from the outside of the system, as described above. Therefore, there is no need to provide in the processor  
25 system a ROM (including a flash memory) to which an IPL program is written in advance.

Also, since an IPL program is downloaded from the

0970808 012904  
FOUO 00000000

outside of the system, there is no need for provision of a special tool, such as a ROM writer, for changing the IPL program. Further, there is no need for provision of a special circuit for accessing a ROM (including a flash memory) added to the processor system to read out an IPL program. If a general-purpose communication method using RS232C or the like is used for the above-described downloading, a personal computer terminal can be used for downloading.

As described above, it is not necessary for the processor system to have a ROM to which an IPL program is written in advance and a special circuit accompanying the ROM. Consequently, the number of components can be reduced and the component mount area can be reduced. Since an IPL program is executed on a RAM connected to the processor system, rewriting of the IPL program can be easily performed at a high speed.

The method of writing an IPL program from the address first read by the CPU immediately after startup when the IPL operation is performed eliminates the need for always writing transferred data to the entire RAM area in a certain situation, e.g., a situation where a CPU start address exists at a lower position in the memory map. Thus, it is possible to start the CPU by only writing a minimized amount of necessary transferred data.

Since writing to the memory is stopped when a



condition is detected which designates a time at which  
IP program transfer should be terminated, undesirable  
or unnecessary writing can be inhibited. For example,  
writing to the memory may be stopped when the amount of  
5 data transferred becomes equal to an amount set in  
advance, thereby inhibiting transfer of an amount of  
data exceeding the size of the RAM area.  
Alternatively, writing to the memory may be stopped  
when a code indicating the end of transfer of a program  
10 is detected, thereby inhibiting transfer of an  
unnecessary amount of data during IPL operation.

Programs (debugging programs) for checking the  
operation of a connected peripheral, for a memory  
check, for checking the operation or condition, e.g.,  
15 the condition of the peripheral connection of a certain  
device, and the like, are written to the memory  
together with an IPL program, and are executed when the  
CPU is activated, thus making it possible to quickly  
find a defective condition of the system.

20 If such debug programs are downloaded from the  
outside of the processor, they can be easily rewritten  
at a high speed.

Thus, it is possible to check whether the  
processor system operates normally before downloading  
25 of the system program to the processor system (before  
starting of the system).

The present invention may be applied to a system

09-01-2009 10:53:10

constituted of a plurality of devices (e.g., a computer  
main unit, an interface device, a display and the like)  
or to a unit formed by one device as long as the  
functions of the above-described embodiments can be  
5 achieved.

Although the present invention has been described  
in its preferred form with a certain degree of  
particularity, many apparently widely different  
embodiments of the invention can be made without  
10 departing from the spirit and scope thereof. It is to  
be understood that the invention is not limited to the  
specific embodiments thereof except as defined in the  
appended claims.

09/0303 012501